
TORUS

TRS-320RGB



IP67 (E







FEATURES

MATERIAL STAINLESS STEEL
WORKING VOLTAGE 24V DC, 100-240V AC

RATED POWER 48/54W

BEAM ANGLE 7°/15°/30°/45°/60°/15°x60°

LAMP LIFE 50,000 HRS

MOUNTING INGROUND SURFACE MOUNTED

DIMENSIONS Ø320x194mm

OPERATION TEMP -20° C - +50° C

BODY COLOR STAINLESS STEEL







ELECTRICAL DATA

POWER CONSUMPTION 48/54W

SUPPLY VOLTAGE 24V DC, 100-240V AC


 COLORS
 RGB


 CONTROL
 DMX512

 CRI
 80+

 LUMEN
 22-25lm /W

DIMENSION









Bullseyes Louver

Honeycomb Louver

ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	VOLTAGE	BEAM ANGLE		IGLE	FINISH	ACCESSORIES		CUSTOM		
TRS 320	48 - 48W	(RGB) RGB	24 - 24V DC	7	-	7°	SS - Stainless Steel	HCL -	Honeycomb Louver	XX	-	XX
	54 - 54W		AC -240V AC	15	-	15°		BL -	Bullseyes Louver			
				30	-	30°						
				45	-	45°						
				60	-	60°						
				15x60	0 - 15	5°x60°						

Sample: TRS 320 $\,$ - $\,$ 48 - RGB - $\,$ 24 - 7 - SS - HCL - XX $\,$