

ATST



YYZ Artiste is a suspended, wall/surface or recessed luminaire that creates an architectural 90° corner. For two-sided illumination around a perimeter, use a wall/surface model. Hang a suspended “L” model for illuminating a wall surface and to provide ambient downlight. Hang a suspended “diamond” model to provide a wide swath of direct ambient downlight.

YYZ Artiste ATST-SM -urface, Wall, Ceiling, Corner Mounted, ATSL-SL-Suspended ‘L’ orientation, ATST-DIA-Suspended ‘DIAMOND’ orientation .

FEATURES


HOUSING	100% RECYCLABLE, EXTRUDED ARCHITECTURAL GRADE T6061 ALUMINIUM
FINISH	ALUMINIUM, BLACK, WHITE, RAL, BRONZE POWDER COAT
RATED POWER	12/13.4/14/22/25/44.6W/Mtr
BEAM ANGLE	120°
MOUNTING	SUSPENDED/ SURFACE MOUNT
OPTIC	OPAL DIFFUSER
DIMENSIONS	96 x 96 mm
OPERATION TEMP	-20° C - +50° C
LAMP LIFE	50,000 HRS
AVAILABLE LENGTH	600, 1200, 1800, 2400, 3000, 3400, 4500, 5000MM
CONTROL	0-10V, 1-10V, DALI, DMX, NON DIMMABLE, PHASE DIM



ELECTRICAL DATA

POWER CONSUMPTION	12W(1100lm/M), 13.4(1573lm/M), 14W(3066lm/M), 22W(5065lm/M), 25W(1263lm/M), 44.6W(1789lm/M), RGBW(371lm/M)
SUPPLY VOLTAGE	220-240 VAC
COLORS	2700K, 3000K, 3500K, 4000K, 5000K, 6500K
CRI	80+/90+

DIMENSION



ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	DRIVER	FINISH	OPTIONS
ARTISTE -ATST - SL	12 - 12W/Mtr	(CT27) 2700K	0-10V	AL - Aluminium natural	EM - 3 Hour Emergency Kit-Remote
ARTISTE -ATST - DIA	13.4 - 13.4W/Mtr	(CT30) 3000K	1-10V	BK - Black powder coat	PIR-A - PIR Absence Detector - remote
ARTISTE -ATST - SM	14 - 14W/Mtr	(CT35) 3500K	DALI	WH - White powder coat	PIR-P - PIR Presence Detector - remote
	22 - 22W/Mtr	(CT40) 4000K	NON DIM	RAL - RAL powder coat	DPIR - DALI PIR Sensor
	25 - 25W/Mtr	(CT50) 5000K	DMX	BR - Bronze powder coat	(XX) - Custom
	44.6 - 44.6W/Mtr	(CT65) 6500K	PHASE DIM		
		(RGBW) RGBW			
		(CTXX) CUSTOM			

Sample: ATST-SL - 12 - CT 27 - 0-10V - AL - EM

MOUNTING OPTIONS



3.5S
Suspended "L" Orientation



3.5DIA
Suspended "DIAMOND" Orientation



3.5SM
Wall, Ceiling or Corner Mount



SUSPENSION HARDWARE

- STD : Standard separate 115mm diameter power canopy and suspension
- COMBO : 115mm diameter canopy and suspension are combined
- SMALL : 82mm diameter small separate power canopy and suspension



STD



COMBO



SMALL