

IVORY SERIES

IVY 86

Mono IP20 CE

YYZ Ivory series of architectural downlight features glare free performance with UGR ≤ 17 even for the ultra wide beam angle. Available in variety of sizes to accommodate wattage range from 10.5W to 50W making it versatile for applications with ceiling heights ranging from 2.8 to 10 meter.

FEATURES

| | |
|-----------------|---------------------------|
| MATERIAL | Die-cast aluminum |
| FINISH | White, Black |
| RATED POWER | 10.5W |
| WORKING VOLTAGE | 24V DC |
| RADIANCE ANGLE | 15°, 24°, 38°, 55° |
| MOUNTING | Ceiling recessed |
| CONNECTION | Indoor rated connections |
| LAMP LIFE | 50,000 Hrs |
| DIMENSION | Ø86 x 55mm (Cutout Ø75mm) |
| OPERATING TEMP | -20° C - +50° C |
| CONTROL | On/Off |



LEDTEEN
LED Quality


24V DC
Working Voltage

10.5W
Rated power

ELECTRICAL DATA

| | |
|-------------------|---------------------|
| POWER CONSUMPTION | 10.5W |
| SUPPLY VOLTAGE | 220-240V AC |
| COLORS | 2700K, 3000K, 4000K |
| CRI | 80, 90 |
| LUMEN | 800lm |

DIMENSIONS



ORDERING LOGIC

| PRODUCT | WATTAGE | COLOR TEMPERATURE | BEAM ANGLE | FINISH | REFLECTOR FINISH | |
|---------|--------------|-------------------|------------|----------|------------------|--------------------|
| IVY 86 | 10.5 - 10.5W | (CT27) | 2700K | 15 - 15° | BK - Black | BL - Black Light |
| | | (CT30) | 3000K | 24 - 24° | WH - White | BS - Bright Silver |
| | | (CT40) | 4000K | 38 - 38° | XX - Custom | BB - Bright Black |
| | | | | 55 - 55° | | BW - Bright White |

Sample: IVY 86 - 10.5 - CT27 - 15 - BK - BL