

IVORY SERIES

IVY 101

Mono IP20 CE

YYZ Ivory series of architectural downlight features glare free performance with UGR ≤ 17 even for the ultra wide beam angle. Available in variety of sizes to accommodate wattage range from 10.5W to 50W making it versatile for applications with ceiling heights ranging from 2.8 to 10 meter.

FEATURES

MATERIAL	Die-cast aluminum
FINISH	White, Black
RATED POWER	15.5W
WORKING VOLTAGE	24V DC
RADIANCE ANGLE	15°, 24°, 38°, 55°
MOUNTING	Ceiling recessed
CONNECTION	Indoor rated connections
LAMP LIFE	50,000 Hrs
DIMENSION	Ø101x 60mm (Cutout Ø90mm)
OPERATING TEMP	-20° C - +50° C
CONTROL	On/Off



LEDTEEN
LED Quality


24V DC
Working Voltage

15.5W
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	15.5W
SUPPLY VOLTAGE	220-240V AC
COLORS	2700K, 3000K, 4000K
CRI	80, 90
LUMEN	1156lm

DIMENSIONS



ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	BEAM ANGLE	FINISH	REFLECTOR FINISH	
IVY 101	15.5 - 15.5W	(CT27)	2700K	15 - 15°	BK - Black	BL - Black Light
		(CT30)	3000K	24 - 24°	WH - White	BS - Bright Silver
		(CT40)	4000K	38 - 38°	XX - Custom	BB - Bright Black
				55 - 55°		BW - Bright White

Sample: IVY 101 - 15.5 - CT27 - 15 - BK - BL