
LATTICE MEDIUM





FEATURES

MATERIAL Aluminum **FINISH** White, Black 2x15/2x20W RATED POWER 220-240V 50/60Hz WORKING VOLTAGE RADIANCE ANGLE Narrow, Medium, Wide Ceiling recessed MOUNTING CONNECTION Indoor rated connections

50,000 Hrs LAMP LIFE

DIMENSION 260 x 130 x 130mm (Cutout 245x115mm)

-20° C - +50° C OPERATIN TEMP On/Off, Triac, 1-10V, Dali CONTROL


ELECTRICAL DATA


POWER CONSUMPTION 2x15/2x20W SUPPLY VOLTAGE 220-240V AC

COLORS 2700K, 3000K, 3500K, 4000K


90+ 95 lm/W LUMEN

DIMENSIONS

















Honey Combo Louver

Linear Spread Lens

Spread Lens

ORDERING LOGIC

LTC-M Series

PRODUCT	COLOR TEM	IPERATURE	CONTROL	VOLTAGE	WATTAGE	BEAM ANGLE	FINISH	ACCESSORIES	CUSTOM
LTC-M	(CT27)	2700K	ON/OFF	240VAC	2x15 - 2x15W	N - Narrow	BL - Black	HCL - Honey Combo Louver	XX
	(CT30)	3000K	TRIAC		2x20 - 2x20W	M - Medium	WH - White	LSL - Linear Spread Lens	
	(CT35)	3500K	1-10V			W - Wide		SL - Spread Lens	
	(CT40)	4000K	DALI						

Sample: LTC-M - CT27 - ON/OFF - 240 - 2x15 - N - BL - HCL - XX

CRI











