GENESIS-ACCENT LIGHTING



GNS-A



IP20 CE

achieve accent or general lighting.

YYZ Genesis downlight features wide range of modular optic within a single fixture that can be combined to produce different light distribution to appeal diverse architectural illumination requirements. These downlights are with symmetric light distribution to

FEATURES

MATERIAL Aluminum **FINISH** White, Black, Grey 11W, 22W, 33W RATED POWER 220-240V 50/60Hz WORKING VOLTAGE

RADIANCE ANGLE Double wash downlight, Double wash, Wall wash,

Accent downlight, Accent oval flood

Ceiling recessed MOUNTING CONNECTION Indoor rated connections

50,000 Hrs

LAMP LIFE

DIMENSION 145 x 129 x 95mm (Cutout Sq124x115mm)

OPERATIN TEMP -20° C - +50° C On/Off, Triac, 1-10V, Dali CONTROL

BINNING SDCM<3

ELECTRICAL DATA

POWER CONSUMPTION 11W, 22W, 33W SUPPLY VOLTAGE 220-240V AC

COLORS 2700K, 3000K, 3500K, 4000K

90+ CRI

Upto 82lumen/W LUMEN





Downlights 3x250mA 36V MAX:33W



Double wallwashers 2x250mA 36V MAX:22W



Wallwashers 250mA 36V MAX:11W



Wallwashers 250mA 36V MAX:11W




Downwards-directed general lighting


250mA 36V MAX:11W



Downwards-directed general lighting 250mA 36V MAX:11W

DIMENSIONS







Darklight



Black

ORDERING LOGIC

PRODUCT	WATTAGE	COLOR [*]	TEMPERATURE	CONTROL	VOLTAGE			OPTIC	FINISH	LOUVER	CUSTOM
GNS-A	11- 11W	(CT27)	2700K	ON/OFF	240VAC	DWDL	- Do	ouble wash Downlight	BL - Black	DL - Dark light	XX
	22 - 22W	(CT30)	3000K	TRIAC		DW	-	Double Wash	WH - White	BL -Black	
	33 - 33W	(CT35)	3500K	1-10V		WW	-	Wall Wash	GR - Grey		
		(CT40)	4000K	DALI		AD	-	Accent Downlight			
						AO	-	Accent Oval Flood			

Sample: GNS-A - 33 - CT27 - ON/OFF - 240 - N - BL - RD - XX

GNA Series