NEUTRINO SERIES





YYZ Neutrino series of architectural downlight features glare free performance with ultra wide beam angle. These ceiling recessed downlights with symmetrical light distribution to achieve an effective task or general lighting. This IP44 rated series is available in square as well as circular versions.

FEATURES


MATERIAL FINISH RATED POWER WORKING CURRENT RADIANCE ANGLE MOUNTING CONNECTION LAMP LIFE DIMENSION OPERATIN TEMP CONTROL Die-cast aluminum White, Black 15W 400mA 12°, 24°, 36° Ceiling recessed Indoor rated connections 50,000 Hrs 119 X 119 x 120mm (Cutout 105x105mm) -20° C - +50° C On/Off, Triac, 1-10V, Dali

ELECTRICAL DATA

POWER CONSUMPTION SUPPLY VOLTAGE COLORS CRI LUMEN 15W 100-240V AC (Remote driver) 2700K, 3000K, 4000K 90 1048 lm @3000K

> () 105x105mm

DIMENSIONS




ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE		BEAM ANGLE			FINISH		
NTN-SQ-B	15 - 15W	(CT27)	2700K	12	-	12°	BK	-	Black
		(CT30)	3000K	24	-	24°	WH	-	White
		(CT40)	4000K	36	-	36°			

Sample: NTN-SQ-B - 15 - CT27 - 12 - BK





CITIZEN LED Quality

400mA Working Current

