

CORAL 5 DOWN LIGHT

CRL 5

Mono IP20/IP65 CE

YYZ Coral recessed LED downlights provides twiced reflection with extremely low glare even in presence of high luminous flux values. This IP65 rated warm LED light source is with aluminum body which provides protection from rain and humidity. It sets standards in terms of visual comfort, efficiency and quality of light for recessed luminaires. This series adopt the best technique of heat conduction, equip with heat resisting optic parts.



FEATURES

MATERIAL	Aluminum
FINISH	White
RATED POWER	42W
WORKING VOLTAGE	100-240V 50/60Hz
RADIANCE ANGLE	55°
MOUNTING	Ceiling recessed
CONNECTION	Indoor & Outdoor rated connections
LAMP LIFE	50,000 Hrs
DIMENSION	Ø230x128mm(Cutout Ø200mm)
OPERATING TEMP	-20° C - +50° C
CONTROL	On/Off, Triac, 1-10V

CITIZEN
LED Quality


240 VOLTS
Working Voltage

42W
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	42W
SUPPLY VOLTAGE	100-240V AC
COLORS	3000K, 4000K, 5000K
CRI	80, 90
LUMEN	3492lm(3000K), 3338lm(4000K), 3536m(5000K)

DIMENSIONS



ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	CONTROL	VOLTAGE	BEAM ANGLE	TRIM FINISH	REFLECTOR FINISH	IP RATING	ACCESSORIES	
CRL5	42 - 42W	(CT30)	3000K	ND - Non Dimmable	240VAC	55 - 55°	WH - White	EL - Electroplate SL - Silver BK - Black GL - Gold	IP20 IP65	XXX
		(CT40)	4000K	TR - TRIAC						
		(CT50)	5000K	AN - 1-10V						

Sample: CRL5 - 42 - CT30 - ND - 240 - 55 - WH - EL - IP20 - XX