WALLWASHER LWO SERIES



LWO-30



IP65 WATER PROOF ϵ

YYZ LWO series linear light is a new solution of large scale high brightness architectural illumination. Its streamline design and aluminum profile along with adjustable brackets make it an elegant solution for wall washing and grazing applications. This IP66 rated modular system is available in 300mm, 500mm, or 1000mm lengths and can be customized as per project situations. Its integrated design of heat dissipating structure and degassing valve make it suitable for exterior architectural, retail and hospitality applications.

FEATURES

LED QUANTITY 30 LED/m

FINISH Machined aluminum WORKING VOLTAGE 24V dc /100-240V ac

RATED POWER 30W/m

BEAM ANGLE 8°, 9°, 15°, 30°, 45°, 60°, 9°x33°, 9°x50°, 10°x60°, 15°x17°, 17°x40°

AVAILABLE LENGTH 300mm, 500mm, 1000mm

MOUNTING

OPTIC

Clear tempered glass

DIMENSIONS

1000(L) x 43.5(W)

OPERATION TEMP

-5° C - +50° C

STORAGE TEMP

-20° C - +60° C

WEIGHT

LAMP LIFE

SURface mounting

Clear tempered glass

1000(L) x 43.5(W)

-5° C - +50° C

600gm/m

50000 hrs

BODY COLOR Black, Light blue, Gray, Gold, White, Custom

CONTROL On/Off, Dali, 1-10V, Dmx

ELECTRICAL DATA

POWER CONSUMPTION 300mm-8W, 500mm-15W, 1000mm-30W


 SUPPLY VOLTAGE
 24V dc / 100-240V ac


 COLORS
 2700K, 3000K, 4000K

CRI 80+ LEDS / 3.3FT 30W/m

LUMEN 63-106m/W @ 4000K

DIMENSION







ORDERING LOGIC

PRODUCT		OPT	IC	COLOR T	EMPARTURE	VOLTAGE	FI	XTURE LENGTH	ВС	DDY COLOR	CUSTOM
LWO30	8	-	8°	(CT27)	2700K	24 - 24VDC	300	- 300mm (8 LEDS)	BK	- BLACK	XX
	9	-	9°	(CT30)	3000K	240 - 240VAC	500	- 500mm (15 LEDS)	LB	- LIGHT BLUE	
	15	-	15°	(CT40)	4000K		1000	- 1000mm (30 LEDS)	GR	- GRAY	
	30	-	30°	(CTXX)	CUSTOM		XX	- CUSTOM	GL	- GOLD	
	45	-	45°						WH	- WHITE	
	60	-	60°						XX	- CUSTOM	
	9x33	-	9° x 33°								
	9x50	-	9°x50°								
	10x60) -	10°x60°								
	15x17	-	15°x17°				9	Sample: LWO-30 - 8 - C	T 27 -	24 - 300 - BK - XX	
	17x40	- 1	.7° x 40°								







