WALLWASHER LWO SERIES



LWO-36



IP66 WATER PROOF ϵ

YYZ LWO series linear light is a new solution of large scale high brightness architectural illumination. Its streamline design and aluminum profile along with adjustable brackets make it an elegant solution for wall washing and grazing applications. This IP66 rated modular system is available in 300mm, 500mm, or 1000mm lengths and can be customized as per project situations. Its integrated design of heat dissipating structure and degassing valve make it suitable for exterior architectural, retail and hospitality applications.

FEATURES

LED QUANTITY 36 Led/mtr

FINISH Machined aluminum

WORKING VOLTAGE 24V dc RATED POWER 36W/mtr

BEAM ANGLE 8°, 10°, 9°x33°, 9°x50°, 10°x60°, 15°, 15°x17°, 17°x40°, 30°, 45°, 60°

AVAILABLE LENGTH 300mm, 500mm, 1000mm

MOUNTING

OPTIC

Clear tempered glass

DIMENSIONS

1000(L) x 43.5(W)

OPERATION TEMP

-5° C - +50° C

STORAGE TEMP

-20° C - +60° C

WEIGHT

LAMP LIFE

SO000 hrs

BODY COLOR Black, Light blue, Gray, Gold, White, Custom

CONTROL On/Off, Dali, Dmx

ELECTRICAL DATA


POWER CONSUMPTION 36W SUPPLY VOLTAGE 24 V dc


COLORS 2700K, 3000K, 4000K

CRI 80+ LEDS / 3.3FT 36W/mtr

LUMEN 63-106lm/W @ 4000K

DIMENSION







ORDERING LOGIC

PRODUCT		OPTIO		COLOR T	EMPARTURE	VOLTAGE	FI	(TURE LENGTH	BC	DDY COLOR	CUS
LWO36	8	-	8°	(CT27)	2700K	24 - 24VDC	300	- 300mm (12 LEDS)	BK	- BLACK	XX
	10	-	10°	(CT30)	3000K		500	- 500mm (18 LEDS)	LB	- LIGHT BLUE	
	15	-	15°	(CT40)	4000K		1000	- 1000mm (36 LEDS)	GR	- GRAY	
	30	-	30°	(CTXX)	CUSTOM		XX	- CUSTOM	GL	- GOLD	
	45	-	45°						WH	- WHITE	
	60	-	60°						XX	- CUSTOM	
	9x33	- 9	9° x 33°								
	9x50	-	9°x50°								
	10x60) - 1	.0°x60°								
	15x17	7 - 1	.5°x17°								7
			7° x 40°					Sample: LWO36 - 8 - C	Т 27 -	24 - 300 - BK - XX	
	XX	- Cl	JSTOM								_







