# OUTDOOR LFX COB SERIES

LFX-O-12.00-CTXX-COB-Z3-420-24-CV-10-H-1-HT-RMTLWL05







YYZ LFX COB IP65 series features excellent homogenous light, without visible light points. The COB strip is a high-density led lighting strip made by COB encapsulation, which can reduce the thermal resistance of the high-density strip circuit system, greatly improves the life of the LED, and the light flux density is high, the glare is small, and the light is uniform. These series is perfect for indirect lighting and hence used in offices, residential interiors, furniture, or places which require large luminous surface.

# FEATURES

LIGHT SOURCE	С
LED QUANTITY	4
FINISH	۷
WORKING VOLTAGE	2
RATED POWER	1
RADIANCE ANGLE	1
LAMP LIFE	5
MOUNTING	3
CONNECTION	Н
CUTTING INCREMENTS	E
DIMENSIONS	5
MAX DAISY RUN	5

COB 420 Leds / mtr White PCB 24 Volts 12W / mtr 180° 50000 hrs 3M Tape on the back Hardwired tails Every 50mm 5000 x 10mm 5 mtr







## ELECTRICAL DATA

POWER CONSUMPTION	12.0W
SUPPLY VOLTAGE	24 Vdc
SUPPLY CURRENT	240V ac
COLORS	2700K, 3000K, 4000K, 5000K, 6000K
CRI	>90
LUMEN	1000-1200lm

## **ORDERING LOGIC**

PRODUCT SERIES	ТҮРЕ	POWER	COLOR TEMPERATUR	LED TYPE	BIN	NO. OF LED	VOLTAGE	CIRCUIT	РСВ	CRI	NO OF LED ROWS	CONNECTIO	N
LFX	O - Outdoor (IP65)	12.00 - 12.0W	(CT27) 2700   (CT30) 3000   (CT40) 4000   (CT50) 5000   (CT60) 6000		Z3	420 - 420 LEDs/mtr	24-24V	CV-Constant voltage	10 - 10mm	H - HIGH (90)	1	HT - Hardwired Tail OC - Outdoor Connector	
			(CT60) 6000					MODEL	COLOR CONTROL	LIGHT EMITTING DIRECTION	LED POWER	PCB COLOR	LENGTH PER REEL
								R - Regular	M - Mono	Т - Тор	L - Low	W - White	L05 - 5mtr

Sample: LFX - O - 12.00 - CT 27 - COB - Z3 - 420 - 24 - CV - 10 - H -1 - HT - RMTLWL05

# OUTDOOR LFX COB SERIES

LFX-O-12.00-CTXX-COB-Z3-420-24-CV-10-H-1-HT-RMTLWL05




### DIMENSIONS



### **BINNING DIAGRAM**

**BIN Details** 

### Binning



### ACCESSORIES

Surface mounted

Hanging installation









Corner installation

Recessed installation





Built-in

installation