

LFX COB NEON SERIES

LFX-O-8.00-CTXX-COB-Z3-320-24-CV-105.5-H-1-HT-RMTLW05

IP67
WATER
PROOF

8.0W

YYZ LFX COB IP67 series features excellent homogenous light, without visible light points. The COB strip is a high-density led lighting strip made by COB encapsulation, which can reduce the thermal resistance of the high-density strip circuit system, greatly improves the life of the LED, and the light flux density is high, the glare is small, and the light is uniform. These series is perfect for indirect lighting and hence used in offices, residential interiors, furniture, or places which require large luminous surface.



FEATURES

LIGHT SOURCE	COB
LED QUANTITY	320 Leds / mtr
FINISH	Black gold
WORKING VOLTAGE	24 Volts
RATED POWER	8W / mtr
RADIANCE ANGLE	180°
LAMP LIFE	50000 hrs
MOUNTING	Clip, Channel
CONNECTION	Outdoor rated connections
CUTTING INCREMENTS	Every 50mm
DIMENSIONS	10x5.5mm
MAX DAISY RUN	5 mtr

- CREE**
LED Quantity
- 24VOLTS**
Working Voltage
- 8W / mtr**
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	8.0W
SUPPLY VOLTAGE	24 Vdc
SUPPLY CURRENT	240V ac
COLORS	2700K, 3000K, 4000K, 5000K, 6000K
CRI	>90
LUMEN	800-1000lm

ORDERING LOGIC

PRODUCT SERIES	TYPE	POWER	COLOR TEMPERATURE	LED TYPE	BIN	NO. OF LED	VOLTAGE	CIRCUIT	WIDTH	CRI	NO OF LED ROWS	CONNECTION
LFX	O - Outdoor (IP67)	08.00 - 8.0W	(CT27) 2700K (CT30) 3000K (CT40) 4000K (CT50) 5000K (CT60) 6000K	COB	Z3	320 - 320 LEDs/mtr	24-24V	CV-Constant voltage	105.5-10x5.5mm	H - HIGH (90)	1	HT - Hardwired Tail OC - Outdoor Connector
MODEL	COLOR CONTROL	LIGHT EMITTING DIRECTION	LED POWER	PCB COLOR	LENGTH PER REEL							
R - Regular	M - Mono	T - Top	L - Low	W - White	L05 - 5mtr							

Sample: LFX - O - 08.00 - CT 27 - COB - Z3 - 320 - 24 - CV - 105.5 - H - 1 - HT - RMTLW05

LFX COB NEON SERIES

LFX-O-8.00-CTXX-COB-Z3-320-24-CV-105.5-H-1-HT-RMTLW05

DIMENSIONS

