OUTDOOR LFX COB SERIES















YYZ LFX COB IP67 series features excellent homogenous light, without visible light points. The COB strip is a high-density led lighting strip made by COB encapsulation, which can reduce the thermal resistance of the high-density strip circuit system, greatly improves the life of the LED, and the light flux density is high, the glare is small, and the light is uniform. These series is perfect for indirect lighting and hence used in offices, residential interiors, furniture, or places which require large luminous surface.



FEATURES

LIGHT SOURCE СОВ

LED QUANTITY 300 Leds / mtr **FINISH** White PCB WORKING VOLTAGE 12 Volts RATED POWER 10W / mtr RADIANCE ANGLE 180° LAMP LIFE 50000 hrs

MOUNTING 3M Tape on the back CONNECTION Hardwired tails **CUTTING INCREMENTS** Every 10mm **DIMENSIONS** 5000 x 10mm MAX DAISY RUN 5 mtr















ELECTRICAL DATA

POWER CONSUMPTION 10.0W SUPPLY VOLTAGE 12 Vdc SUPPLY CURRENT 240V ac

2700K, 3000K, 4000K, 5000K, 6000K **COLORS**

CRI LUMEN 700-950lm

ORDERING LOGIC

LFX O - Outd	oor 10.00 - 10.0W	(CT27) 2700K	СОВ							ROWS		
		(CT30) 3000K (CT40) 4000K (CT50) 5000K (CT60) 6000K	СОВ	Z3	300 - 300 LEDs/mtr	12-12V	CV-Constant voltage	10 - 10mm	H - HIGH (90)	1	HT - Hardwire OC - Outdoor	
		(CT60) 6000K					MODEL	COLOR CONTROL	LIGHT EMITTING DIRECTION	LED POWER	PCB COLOR	LENGTH PER REEL
							R - Regular	M - Mono	T - Top	L - Low	W - White	L05 - 5mtr

Sample: LFX - O - 10.00 - CT 27 - COB - Z3 - 300 - 12 - CV - 10 - H -1 - HT - RMTLWL05






DIMENSIONS



BINNING DIAGRAM

BIN Details



ACCESSORIES

Surface mounted









Hanging installation

2020B

Corner installation



1616B

Recessed installation



Built-in installation