OUTDOOR **LFX COB SERIES**

LFX-O-10.00-CTXX-COB-Z3-512-24-CV-08-H-1-HT-RMTLWL05





YYZ LFX COB IP67 series features excellent homogenous light, without visible light points. The COB strip is a high-density led lighting strip made by COB encapsulation, which can reduce the thermal resistance of the high-density strip circuit system, greatly improves the life of the LED, and the light flux density is high, the glare is small, and the light is uniform. These series is perfect for indirect lighting and hence used in offices, residential interiors, furniture, or places which require large luminous surface.

FEATURES

LIGHT SOURCE
LED QUANTITY
FINISH
WORKING VOLTAGE
RATED POWER
RADIANCE ANGLE
LAMP LIFE
MOUNTING
CONNECTION
CUTTING INCREMENTS
DIMENSIONS
MAX DAISY RUN

COB 512 Leds / mtr White PCB 24 Volts 10W / mtr 180° 50000 hrs 3M Tape on the back Hardwired tails Every 62.50mm 5000 x 8mm 5 mtr





ELECTRICAL DATA

POWER CONSUMPTION	10.0W
SUPPLY VOLTAGE	24 Vdc
SUPPLY CURRENT	240V ac
COLORS	2700K, 3000K, 4000K, 5000K, 6000K
CRI	>90
LUMEN	1000-1100lm

ORDERING LOGIC

(IP67) (CT30) 3000K LEDs/mtr voltage OC - (CT40) 4000K (CT50) 5000K (CT60) 6000K LIGHT LED PCB	HT - Hardwired Tail OC - Outdoor Connector
LIGHT MODEL COLOR EMITTING LED PCB	
CONTROL DIRECTION POWER COL	PCB LENGTH COLOR PER REEL
R - Regular M - Mono T - Top L - Low W - 1	W - White L05 - 5mtr

Sample: LFX - O - 10.00 - CT 27 - COB - Z3 - 512 - 24 - CV - 08 - H - 1 - HT - RMTLWL05



IP 67(Diamond) D



OUTDOOR LFX COB SERIES

LFX-O-10.00-CTXX-COB-Z3-512-24-CV-08-H-1-HT-RMTLWL05




DIMENSIONS



BINNING DIAGRAM

BIN Details

Binning



ACCESSORIES

Surface mounted

Hanging installation









Corner installation

Recessed installation





Built-in installation

