OUTDOOR LFX COB SERIES















YYZ LFX COB IP67 series features excellent homogenous light, without visible light points. The COB strip is a high-density led lighting strip made by COB encapsulation, which can reduce the thermal resistance of the high-density strip circuit system, greatly improves the life of the LED, and the light flux density is high, the glare is small, and the light is uniform. These series is perfect for indirect lighting and hence used in offices, residential interiors, furniture, or places which require large luminous surface.



FEATURES

LIGHT SOURCE СОВ

LED QUANTITY 600 Leds / mtr **FINISH** White PCB WORKING VOLTAGE 24 Volts RATED POWER 10W / mtr RADIANCE ANGLE 180° LAMP LIFE 50000 hrs

MOUNTING 3M Tape on the back CONNECTION Hardwired tails **CUTTING INCREMENTS** Every 10mm **DIMENSIONS** 5000 x 10mm MAX DAISY RUN 5 mtr









IP 67(Diamond)



ELECTRICAL DATA

POWER CONSUMPTION 10.0W SUPPLY VOLTAGE 24 Vdc SUPPLY CURRENT 240V ac

2700K, 3000K, 4000K, 5000K, 6000K **COLORS**

CRI LUMEN 700-950lm

ORDERING LOGIC

LFX O-0		TEMPERATURE			NO. OF LED	VOLTAGE	CIRCUIT	PCB	CRI	NO OF LED ROWS	CONNECTION	
LFX O - Outdoo (IP67)		(CT27) 2700P (CT30) 3000P (CT40) 4000P (CT50) 5000P (CT60) 6000P		Z3	600 - 600 LEDs/mtr	24-24V	CV-Constant voltage	10 - 10mm	H - HIGH (90)	1 HT - Hardwired Tail OC - Outdoor Conn		
		(CT60) 6000F					MODEL	COLOR CONTROL	LIGHT EMITTING DIRECTION	LED POWER	PCB COLOR	LENGTH PER REEL
							R - Regular	M - Mono	Т - Тор	L - Low	W - White	L05 - 5mtr

Sample: LFX - O - 10.00 - CT 27 - COB - Z3 - 600 - 24 - CV - 10 - H -1 - HT - RMTLWL05






DIMENSIONS



BINNING DIAGRAM

BIN Details



ACCESSORIES

Surface mounted Hanging installation Corner installation Recessed installation installation

1013 1708 1715 2020 2020B 1616 1616B 2408 2415 2126