OUTDOOR LFX COB SERIES

LFX-O-12.00-CTXX-COB-Z3-360-12-CV-10-H-1-HT-RMTLWL05



CRI 90



YYZ LFX COB IP67 series features excellent homogenous light, without visible light points. The COB strip is a high-density led lighting strip made by COB encapsulation, which can reduce the thermal resistance of the high-density strip circuit system, greatly improves the life of the LED, and the light flux density is high, the glare is small, and the light is uniform. These series is perfect for indirect lighting and hence used in offices, residential interiors, furniture, or places which require large luminous surface.



FEATURES

LIGHT SOURCE
LED QUANTITY
FINISH
WORKING VOLTAGE
RATED POWER
RADIANCE ANGLE
LAMP LIFE
MOUNTING
CONNECTION
CUTTING INCREMENTS
DIMENSIONS
MAX DAISY RUN

COB 360 Leds / mtr White PCB 12 Volts 12W / mtr 180° 50000 hrs 3M Tape on the back Hardwired tails Every 25mm 2500 x 10mm 2.5 mtr



IP 67(Diamond)

ELECTRICAL DATA

POWER CONSUMPTION	12.0W
SUPPLY VOLTAGE	12 Vdc
SUPPLY CURRENT	240V ac
COLORS	2700K, 3000K, 4000K, 5000K, 6000K
CRI	>90
LUMEN	820-1050lm

ORDERING LOGIC

PRODUCT SERIES	ТҮРЕ	POWER	COLOR TEMPERATURE		LED TYPE	BIN	NO. OF LED	VOLTAGE	CIRCUIT	РСВ	CRI	NO OF LED ROWS	CONNECTIO	N
LFX	O - Outdoor (IP67)	12.00 - 12.0W	(CT30) (CT40) (CT50)	3000K 4000K 5000K	СОВ	Z3	360 - 360 LEDs/mtr	12-12V	CV-Constant voltage	10 - 10mm	H - HIGH (90)	1	HT - Hardwird OC - Outdoor	
			(C160)	6000K					MODEL	COLOR CONTROL	LIGHT EMITTING DIRECTION	LED POWER	PCB COLOR	LENGTH PER REEL
									R - Regular	M - Mono	Т - Тор	L - Low	W - White	L05 - 5mtr

Sample: LFX - O - 12.00 - CT 27 - COB - Z3 - 360 - 12 - CV - 10 - H - 1 - HT - RMTLWL05


OUTDOOR LFX COB SERIES

LFX-O-12.00-CTXX-COB-Z3-360-12-CV-10-H-1-HT-RMTLWL05



DIMENSIONS






BINNING DIAGRAM

BIN Details





ACCESSORIES

Surface mounted

Hanging installation









Corner installation



Recessed installation





Built-in installation

