OUTDOOR LFX COB SERIES















YYZ LFX COB IP67 series features excellent homogenous light, without visible light points. The COB strip is a high-density led lighting strip made by COB encapsulation, which can reduce the thermal resistance of the high-density strip circuit system, greatly improves the life of the LED, and the light flux density is high, the glare is small, and the light is uniform. These series is perfect for indirect lighting and hence used in offices, residential interiors, furniture, or places which require large luminous surface.



FEATURES

LIGHT SOURCE СОВ

LED QUANTITY 480 Leds / mtr **FINISH** White PCB WORKING VOLTAGE 24 Volts RATED POWER 15W / mtr RADIANCE ANGLE 180° LAMP LIFE 50000 hrs

MOUNTING 3M Tape on the back CONNECTION Hardwired tails **CUTTING INCREMENTS** Every 50mm **DIMENSIONS** 5000 x 10mm MAX DAISY RUN 5 mtr













ELECTRICAL DATA

POWER CONSUMPTION 15.0W 24 Vdc SUPPLY VOLTAGE SUPPLY CURRENT 240V ac

2700K, 3000K, 4000K, 5000K, 6000K **COLORS**


CRI

LUMEN 1300-1500lm

ORDERING LOGIC

			₹E		NO. OF LED	VOLTAGE	CIRCUIT	РСВ	CRI	NO OF LED ROWS	CONNECTION	
- Outdoor (IP67)	15.00 - 15.0W	(CT27) 2700 (CT30) 3000 (CT40) 4000 (CT50) 5000 (CT60) 6000	iK iK iK	Z3	480 - 480 LEDs/mtr	24-24V	CV-Constant voltage	10 - 10mm	H - HIGH (90)	1	HT - Hardwire OC - Outdoor (
		(C100) 600	ır.				MODEL	COLOR CONTROL	LIGHT EMITTING DIRECTION	LED POWER	PCB COLOR	LENGTH PER REEL
							R - Regular	M - Mono	Т - Тор	L - Low	W - White	L05 - 5mtr

Sample: LFX - O - 15.00 - CT 27 - COB - Z3 - 480 - 24 - CV - 10 - H -1 - HT - RMTLWL05






DIMENSIONS



BINNING DIAGRAM

BIN Details



ACCESSORIES

Surface mounted











Hanging installation

2020B

Corner installation

1616



Recessed installation





