
FLOOD LIGHT

RFL-RGB/RGBW



IP66 WATER ϵ



FEATURES

MATERIAL Anodized extruded aluminum

FINISH Black
RATED POWER 180W
WORKING VOLTAGE 220 Vac
LED QUANTITY 84Nos

BEAM ANGLE 8°, 15°, 20°, 35°, 45°, 60°

ROTATION ANGLE 130°

MOUNTING Surface mount

CONNECTION Outdoor rated connections

LAMP LIFE 50,000 hrs

DIMENSIONS 423mm(L)x188mm(W)x276mm(H)

OPERATION TEMP -40° C $-+50^{\circ}$ C STORAGE TEMP -40° C $-+80^{\circ}$ C

CONTROL DMX

ELECTRICAL DATA

POWER CONSUMPTION 180W
SUPPLY VOLTAGE 220 Vac
COLORS RGB, RGBW

CRI >80


LUMENS 23-26lm/W RGB, 49-53lm/W RGBW


CREE






DRAWING







ORDERING LOGIC

RFL

PRODUCT	WATTAGE	COLOR TEMPERATURE		OPTIC		VOLTAGE		FINISH		CUSTOM	
RFL	180 - 180W	(RGB)	RGB	8	-	8°	220 -	220V AC	BK -	Black	XX - XXX
		(RGBW)	RGBW	15	-	15°					
				20	-	20°					
				35	-	35°					
				45	-	45°					
				60	-	60°					

Sample: RFL -180 - RGB - 8 - 220 - BK - XX