

HERMETIC 2

HMT 2

Mono IP66 CE

YYZ Hermetic is a tough and corrosion resistant surface/suspended mounted weatherproof luminaire suitable for high humidity areas or exterior mounting under a canopy or covered environment. It provides better wide-beam light distribution for straight forward and effective lighting. This fixture is equipped with stainless steel tamper resistant clips with IP66 rating makes it preferred solution for car parks, back of house, warehouse applications, etc.

FEATURES

HOUSING	RAL 7035 Light grey polycarbonate
FINISH	Grey polycarbonate
RATED POWER	18/24/30/36/45/50/65W
WORKING VOLTAGE	220-240V ac 50/60Hz
BEAM ANGLE	120°
MOUNTING	Surface mounted
LAMP LIFE	50,000 hrs
AMBIENT TEMPERATURE	-20° C - +50° C
CONTROL	On-Off, 1-10V, Dali
LUMEN	125 lm/W
OPTIC	Polycarbonate diffuser



LG LED Quality

220-240VAC Working Voltage

18/24/30/36/45/50/65W Rated power

ELECTRICAL DATA

POWER CONSUMPTION	18/24/30/36/45/50/65W
SUPPLY VOLTAGE	220-240V ac 50/60Hz
CCT	2700, 3000K, 4000K, 5000K, 5700K, 6500K
CRI	80+

ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	DRIVER	FIXTURE SIZE -L x W x H
HMT 2	18 - 18W	(CT27) 2700K	ND - Non-Dimmable	18W - 607 x 71 x 74mm
	24 - 24W	(CT30) 3000K	AN - 1-10V	24W - 607 x 116 x 74mm
	30 - 30W	(CT40) 4000K	DA - Dali	30W - 1207 x 71 x 74mm
	36 - 36W	(CT50) 5000K		45W - 1525 x 71 x 74mm
	45 - 45W	(CT57) 5700K		18W, 36W - 1207 x 91 x 78mm
	50 - 50W	(CT65) 6500K		30W, 45W - 1507 x 91 x 78mm
	65 - 65W	(CTX) CUSTOM		36W, 50W - 1027 x 116 x 74mm
				45W, 65W - 1507 x 116 x 74mm

Sample: HMT2 - 18 - CT27 - ND - 18W