

HERMETIC 4

HMT 4

Mono IP66 CE

YYZ Hermetic is a tough and corrosion resistant surface/suspended mounted weatherproof luminaire suitable for high humidity areas or exterior mounting under a canopy or covered environment. It provides better wide-beam light distribution for straight forward and effective lighting. This fixture is equipped with stainless steel tamper resistant clips with IP66 rating makes it preferred solution for car parks, back of house, warehouse applications, etc.

FEATURES

HOUSING	RAL 7035 Light grey polycarbonate
FINISH	Grey polycarbonate
RATED POWER	100W, 120Wm, 150W
WORKING VOLTAGE	100-277V AC / 200-480V AC 50/60Hz
BEAM ANGLE	120°
MOUNTING	Surface mounted
LAMP LIFE	50,000 hrs
DIMENSIONS	1280 x 334 x 140mm
AMBIENT TEMPERATURE	-20° C - +50° C
CONTROL	On-Off, 1-10V, Dali
LUMEN	150 lm/W
OPTIC	Polycarbonate diffuser



LG LED Quality

100-277/220-480VAC Working Voltage

100/120/150W Rated power

ELECTRICAL DATA

POWER CONSUMPTION	100/120/150W
SUPPLY VOLTAGE	100-277V AC / 200-480V AC 50/60Hz
CCT	2700, 3000K, 4000K, 5000K, 5700K, 6500K
CRI	80+

ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	DRIVER
HMT 4	100 - 100W	(CT27) 2700K	ND - Non-Dimmable
	120 - 120W	(CT30) 3000K	AN - 1-10V
	150 - 150W	(CT40) 4000K	DA - Dali
		(CT50) 5000K	
		(CT57) 5700K	
		(CT65) 6500K	
		(CTXX) CUSTOM	

Sample: HMT4 - 100 - CT27 - ND