# **CHAMAELEO RESIDENTIAL SERIES**





IP20,44 (€

 ${\it YYZ\,Chamae leo\,Residential\,series}, perfect spot \, lighting\, or\, accentuation\, with\, an\, almost\, invisible\, light \, aperture$ is ideally achieved. Super modular design with numerous mounting rings, round as well as square designs with adjustable and fixed options, in various wattages enable nuanced adaptation to different needs. Honey combo filter can be added to provide maximum visual comfort.

#### **FEATURES**

LED QUANTITY 1 Led FINISH White

WORKING CURRENT 250mA (9W), 350mA (13W)

RATED POWER 9/13W

RADIANCE ANGLE 15°, 24°, 38°, 55° 50,000 hrs LAMP LIFE MOUNTING Ceiling recessed

CONNECTION Indoor rated connections Ø75 x 102.4mm, 75x75mm **DIMENSIONS** 

OPERATION TEMP -20° C - +50° C

On/Off, Phase, 1-10V, Dali CONTROL


#### **ELECTRICAL DATA**


POWER CONSUMPTION 9/13W SUPPLY VOLTAGE 220-240V ac

COLORS 2700K, 3000K, 4000K

80,90 CRI 80lm/W LUMEN

### **DIMENSIONS**





## **ORDERING LOGIC**

PRODUCT	WATTAGE	COLOR TEMPERATURE	CONTROL	CURRENT	BEAM	ANGLE	CRI	FINISH	ACCESSORY	CUSTOM
CMO RS-RF02	9 - 9W	(CT27) 2700K	ND - ON/OFF	250 - 250mA(9W)	15	- 15°	80 - 80	WH - White	HC - Honey Comb	XX
	13 - 13W	(CT30) 3000K	PH - PHASE	350 - 350mA(13W)	24	- 24°	90 - 90		SL - Soft Lens	
		(CT40) 4000K	AN - 1-10V		38	- 38°				
			DA - DALI		55	- 55°				

Sample: CMO RS-RF02 -9 -CT27 - ND - 250 - 15 - 80 - WH - HC - XX













