

LINEAR WALLWASHER PRO SERIES

LWW PRO-OM RGB/RGBW



YYZ LWW series linear light is a new solution of large scale high brightness architectural illumination. Its streamline design and aluminum profile along with adjustable brackets make it an elegant solution for wall washing and grazing applications. This IP66 rated modular system is available in 300mm, 500mm, or 1000mm lengths and can be customized as per project situations. Its integrated design of heat dissipating structure and degassing valve make it suitable for exterior architectural, retail and hospitality applications.

FEATURES

LED QUANTITY	12 Led/ft
FINISH	6063 High density aluminum
WORKING VOLTAGE	100-277 V ac 50/60Hz
RATED POWER	16/24/48W
BEAM ANGLE	20°, 35°, 50°. 10x40°
AVAILABLE LENGTH	410mm, 605mm, 1190mm
MOUNTING	Surface mounting
OPTIC	Clear tempered glass
DIMENSIONS	410, 605, 1190(L) x 50(B) x 69.3(H)
OPERATION TEMP	-40° C - +50° C
STORAGE TEMP	-40° C - +85° C
LAMP LIFE	50,000 hrs
BODY COLOR	Black, Grey, White
CONTROL	DMX



CREE / NICHIA
LED Quality

100-240 VAC
Working Voltage

16 W (410mm), 24 W(605mm)
48 W(1190mm)
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	410mm-16W, 605mm-24W, 1190mm-48W
SUPPLY VOLTAGE	100-240 V ac 50/60Hz
COLORS	RGB, RGBW
CRI	80, 90+



DIMENSION



ORDERING LOGIC


PRODUCT	POWER	OPTIC	COLOR TEMPERATURE	CONTROL	VOLTAGE	FIXTURE LENGTH	BODY COLOR	CUSTOM
LWW PRO-OM	16 - 16W (410mm)	20 - 20°	(RGB) RGB	DX - DMX	240 - 100-240VAC	410 - 410mm (16W)	BK - BLACK	XX
	24 - 24W (605mm)	35 - 35°	(RGBW) RGBW			605 - 605mm (24W)	GR - GREY	
	48 - 48W (1190mm)	50 - 50°				1190 - 1190mm (48W)	WH - WHITE	
		10-40 - 10° x 40°						

Sample: LWWPRO-OM- 16 - 20 - RGB - DX - 240 - 410 - BK - XX


LINEAR WALLWASHER PRO SERIES

LWW PRO-OM RGB/RGBW



ANTI-GLARE ACCESSORIES




Item: YYZAGS-410/605/1190
Anti-glare shield




Height with/without mounting bracket (YYZMBA-H81)




Item: YYZGLA-410/605/1190-RGBW
Asymmetric anti-glare louver




Height with/without mounting bracket (YYZMBA-H81)





Item: YYZGLS-410/605/1190-RGBW
Symmetric anti-glare louver



Height with/without mounting bracket (YYZMBA-H81)



Item: YYZMBA-H81
Description: YYZMBA-H81 is an adjustable mounting option are used for applications that require angle adjustments. It can rotate up to 180°



EXTENSION CABLE

DMX



Item: YYZACF-300-3pin
3-pin 300mm female Power lead in cable to bare wire



Item: YYZDCAPAC-3pin-M
3-pin cable male cable end cap



Item: YYZACL-020-3pin
3-pin 2 meters male to female extension cable



Item: YYZACL-100-3pin
3-pin 10 meters male to female extension cable

YYZ P0427(65).35



Item: YYZDCF-300-3pin
3-pin 300mm female lead in cable to bare wire



Item: YYZDCAP-3pin-M
3-pin cable male cable end cap/DMX Terminator



Item: YYZ-XLR-ECDCF
XLR-3 connector to 3-pin female connector. Customized DMX data lead in cable which connects the DMX controller with XLR-3 sockets to the first fixture of the daisy chain



Item: YYZDCL-020-3pin
3-pin 2 meters male to female extension cable



Item: YYZDCL-100-3pin
3-pin 10 meters male to female extension cable