

NEUTRINO-R

NTN-R

Mono IP44 CE

YYZ Neutrino-R adjustable lights are miniature downlights in aluminum housing which are designed for wet area applications like jacuzzi, toilets, balcony, exterior entrance that demands water proof construction and resistance to corrosion. These recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or ambient lighting.

FEATURES

MATERIAL	Aluminum
FINISH	Black, Silver, White
RATED POWER	12W, 15W
WORKING VOLTAGE	100-240V ac
RADIANCE ANGLE	15°, 24°, 36°
MOUNTING	Ceiling recessed
CONNECTION	Indoor rated connections
LAMP LIFE	50,000 Hrs
DIMENSION	Ø116 x 125mm(CutoutØ108mm)
OPERATING TEMP	-30° C - +50° C
CONTROL	On/Off, 1-10V, Dali, Triac
OPTICS	Lens



CITIZEN
LED Quality

240V AC
Working Voltage

12W/15W
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	12W, 15W
SUPPLY VOLTAGE	100-240V ac
COLORS	2700K, 3000K, 3700K, 4000K, 5000K
CRI	90
LUMEN	95lm/W

DIMENSIONS



ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	CONTROL	VOLTAGE	BEAM ANGLE	FINISH	ACCESSORIES	CUSTOM	
NTN-R	12 - 12W	(CT27)	2700K	SW - On/Off	AC - 240V ac	15 - 15°	WH - White	FG - Frosted Glass CG - Clear Glass	xx
	15 - 15W	(CT30)	3000K	AN - 1-10V		24 - 24°	BK - Black		
		(CT37)	3700K	DA - Dali		36 - 36°	SL - Silver		
		(CT40)	4000K	TR - Triac					
		(CT50)	5000K						

Sample: NTN-RA - 12 - CT27 - SW - AC - 15 - WH - FG - XX