

LIMO 2

LMO 2

Mono IP65 CE

YYZ Limo series are designed for wall mounted application with beam up/down or one sided, Constructed in die-cast aluminium, with rugged IP65 rating makes it suited for indoor/outdoor rated applications. Options of beam angles to suit the application area.



FEATURES

HOUSING	Die-cast aluminum
WORKING CURRENT	350mA
MOUNTING	Surface mounted
BEAM ANGLE	24° . 36°
DIMENSIONS	Ø90x200mm
OPERATION TEMP	-20° C - +50° C
BODY COLOR	Black, Silver, White
LAMP LIFE	50,000 hrs
CONTROL	On/Off

CREE
LED Quality


350mA
Working Current

2x15W
Rated power

ELECTRICAL DATA

RATED POWER	2x15W
COLORS	3000K, 4000K, 5000K
CRI	80
LUMEN OUTPUT	2x1052 lm

DIMENSION



ORDERING LOGIC

PRODUCT	WATTAGE	OPTIC	COLOR TEMPERATURE	FINISH	CUSTOM
LMO 2	30 - 2x15W	24 - 24° (CT30)	3000K	BK - Black	XX - XXX
		36 - 36° (CT40)	4000K	SL - Silver	
		(CT50)	5000K	WH - White	

Sample: LMO 2 - 30 - 24 - CT 30 - BK - XX