

# LIMO 4

## LMO 4

Mono IP65 CE

YYZ Limo series are designed for wall mounted application with beam up/down or one sided, Constructed in die-cast aluminium, with rugged IP65 rating makes it suited for indoor/outdoor rated applications. Options of beam angles to suit the application area.



### FEATURES

HOUSING	Die-cast aluminum
WORKING CURRENT	500mA, 700mA
MOUNTING	Surface mounted
BEAM ANGLE	24° . 36°
DIMENSIONS	Ø150x350mm
OPERATION TEMP	-20° C - +50° C
BODY COLOR	Black, Silver, White
LAMP LIFE	50,000 hrs
CONTROL	On/Off

CREE  
LED Quality


500mA /700mA  
Working Current

2x20W /2x30W  
Rated power

### ELECTRICAL DATA

RATED POWER	2x20W, 2x30W
COLORS	3000K, 4000K, 5000K
CRI	80
LUMEN OUTPUT	2x1537 lm @ 2x20W, 2x2055 lm @ 2x30W

### DIMENSION



### ORDERING LOGIC

PRODUCT	WATTAGE	OPTIC	COLOR TEMPERATURE	FINISH	CUSTOM
LMO 4	40 - 2x20W	24 - 24°	(CT30) 3000K	BK - Black	XX - XXX
	60 - 2x30W	36 - 36°	(CT40) 4000K	SL - Silver	
			(CT50) 5000K	WH - White	

Sample: LMO 4 - 40 - 24 - CT 30 - BK - XX