LINEAR WALLWASHER

LRW38-RGB/RGBW



IP66 WATER ϵ

YYZ LRW is wall washer series linear light of new solution for large scale with high brightness architectural illumination. Its streamline design and aluminum profile along with adjustable brackets make it an elegant solution for wall washing and grazing applications. This IP66 rated modular system is available in 300mm, 500mm, or 1000mm lengths and can be customized as per project situations. Its integrated design of heat dissipating structure and degassing valve make it suitable for exterior architectural, retail and hospitality applications.

FEATURES

FINISH 6063 Aluminum

WORKING VOLTAGE 24V dc RATED POWER 36W/mtr

BEAM ANGLE 7°, 15°, 30°, 45°, 60°, 15°x60°, 20°x40°

MOUNTING Surface mounting

OPTIC PC

DIMENSIONS 1000(L) x 38(W) x 57.2(H)mm

 OPERATION TEMP
 -25° C - +50° C

 STORAGE TEMP
 -40° C - +80° C

WEIGHT 1.5kg LAMP LIFE 50000 HRS

BODY COLOR Black, Grey, White, Green

CONTROL Dmx512









ELECTRICAL DATA

SUPPLY VOLTAGE 24V dc
COLORS RGB, RGBW

LUMEN 44.5-45lm/W @ RGB, 49-50lm/W @ RGBW

DIMENSION









ORDERING LOGIC

PRODUCT	WATTAGE		COLOR TEMPERATURE		VOLTAGE	BEAM		GLE	BODY COLOR			ACCESSORIES		CUSTOM
LRW38	36 -	36W	(RGB)	RGB	DC - 24VDC	7	-	7°	BK	-	Black	LL - Lon	gitudinal Louvers	XX - XXX
			(RGBW)	RGBW		15	-	15°	GR	-	Grey	LB -	Light Baffle	
						30	-	30°	WH	-	White	SB - Ser	micircle Bull's-eye	
						45	-	45°	GN	-	Green			
						60	-	60°						
						15x60	- 1	5°x60°						
						20x40	- 2	0°x40°						

Sample: LRW38 - 36 - RGB - DC - 7 - BK - LL - XX