LINEAR WALLWASHER

LRW38H-RGBW



IP66 WATER ϵ

YYZ LRW is wall washer series linear light of new solution for large scale with high brightness architectural illumination. Its streamline design and aluminum profile along with adjustable brackets make it an elegant solution for wall washing and grazing applications. This IP66 rated modular system is available in 300mm, 500mm, or 1000mm lengths and can be customized as per project situations. Its integrated design of heat dissipating structure and degassing valve make it suitable for exterior architectural, retail and hospitality applications.

FEATURES

FINISH 6063 Aluminum

WORKING VOLTAGE 24V dc RATED POWER 48W/mtr

BEAM ANGLE 15°, 30°, 45°, 15°x60°, 20°x40°

MOUNTING Surface mounting

OPTIC PC

DIMENSIONS 1000(L) x 38(W) x86(H)mm

OPERATION TEMP -25° C $- +50^{\circ}$ C STORAGE TEMP -40° C $- +80^{\circ}$ C

WEIGHT 2.4kg LAMP LIFE 50000 hrs

BODY COLOR Black, Grey, White, Green

CONTROL Dmx512









ELECTRICAL DATA

SUPPLY VOLTAGE 24V dc COLORS RGBW

LUMEN 38-39.5lm/W @ 48W RGBW

DIMENSION









ORDERING LOGIC

PRODUCT	WATTAGE		COLOR TEMPERATURE		VOLTAGE	BEAMANGLE			BODY COLOR			ACCESSORIES		CUSTOM
LRW38H	48 -	48W	(RGBW)	RGBW	DC - 24V DC	15	-	15°	BK	-	Black	LL - Lor	ngitudinal Louvers	XX - XXX
						30	-	30°	GR	-	Grey	LB -	Light Baffle	
						45	-	45°	WH	-	White			
						15x60	-	15°x60°	GN	-	Green			
						20x40	-	20°x40°						

Sample: LRW38H - 48 - RGBW - DC -15 - BK - LL - XX