LINEAR WALLWASHER



LRW65-Mono



IP66 WATER PROOF

CE

YYZ LRW is wall washer series linear light of new solution for large scale with high brightness architectural illumination. Its streamline design and aluminum profile along with adjustable brackets make it an elegant solution for wall washing and grazing applications. This IP66 rated modular system is available in 300mm, 500mm, or 1000mm lengths and can be customized as per project situations. Its integrated design of heat dissipating structure and degassing valve make it suitable for exterior architectural, retail and hospitality applications.

FEATURES

FINISH 6063 Aluminum WORKING VOLTAGE 100-240V ac RATED POWER 60W/mtr

BEAM ANGLE 7°, 15°, 22°, 30°, 45°, 60°, 15°x60°, 20°x40°

MOUNTING Surface mounting

OPTIC PC

DIMENSIONS 1000(L) x 65(W) x16(H)mm

 OPERATION TEMP
 -25° C - +50° C

 STORAGE TEMP
 -40° C - +80° C

WEIGHT 3.5kg LAMP LIFE 50000 hrs

BODY COLOR Black, Grey, White, Green

CONTROL Dmx512








ELECTRICAL DATA


SUPPLY VOLTAGE 100-240V ac

COLORS 2700K, 3000K, 4000K, 5000K, 6000K

LUMEN 69.8-70.1lm/W

DIMENSION









ORDERING LOGIC

PRODUCT	WATTAGE		COLOR TEMPERATURE		VOLTAGE	BEAMANGLE		BODY COLOR		ACCESSORIES		CUSTOM		
LRW65	60 -	60W	(CT27)	2700K	AC - 240V AC	7	-	7°	BK	-	Black	LL - Lo	ongitudinal Louvers	XX - XXX
			(CT30)	3000K		15	-	15°	GR	-	Grey	LB -	Light Baffle	
			(CT40)	4000K		22	-	22°	WH	-	White			
			(CT50)	5000K		30	-	30°	GN	-	Green			
			(CT60)	6000K		45	-	45°						
						60	-	60°						
						15x60) -	15°x60°						
						20x4	0 -	20°x40°						

Sample: LRW65 - 60 - CT27 - AC -7 - BK - LL - XX