## **LINEAR WALLWASHER**

# LRW65-RGB/RGBW



IP66

 $\epsilon$ 

YYZ LRW is wall washer series linear light of new solution for large scale with high brightness architectural illumination. Its streamline design and aluminum profile along with adjustable brackets make it an elegant solution for wall washing and grazing applications. This IP66 rated modular system is available in 300mm, 500mm, or 1000mm lengths and can be customized as per project situations. Its integrated design of heat dissipating structure and degassing valve make it suitable for exterior architectural, retail and hospitality applications.

# and the last of th

### **FEATURES**

FINISH 6063 Aluminum WORKING VOLTAGE 100-240V ac RATED POWER 60W/mtr

BEAM ANGLE 7°, 15°, 22°, 30°, 45°, 60°, 15°x60°, 20°x40°

MOUNTING Surface mounting

OPTIC PC

DIMENSIONS 1000(L) x 65(W) x16(H)mm

 OPERATION TEMP
 -25° C - +50° C

 STORAGE TEMP
 -40° C - +80° C

WEIGHT 3.5kg LAMP LIFE 50000 hrs

BODY COLOR Black, Grey, White, Green

CONTROL Dmx512









### **ELECTRICAL DATA**

SUPPLY VOLTAGE 100-240V ac COLORS RGB, RGBW

LUMEN 24.95-25.35lm/W @ RGB, 34.8-35.35lm/W @ RGBW

# DIMENSION









### **ORDERING LOGIC**

PRODUCT	WATTAGE		COLOR TEMPERATURE		VOLTAGE	BEAMANGLE			BODY COLOR			ACCESSORIES		CUSTOM
LRW65	60 -	60W	(RGB)	RGB	AC - 240V AC	7	-	7°	BK	-	Black	LL - Loi	ngitudinal Louvers	XX - XXX
			(RGBW)	RGBW		15	-	15°	GR	-	Grey	LB -	Light Baffle	
						22	-	22°	WH	-	White			
						30	-	30°	GN	-	Green			
						45	-	45°						
						60	-	60°						
						15x60	-	15°x60°						
						20x40	-	20°x40°						

Sample: LRW65 - 60 - RGB - AC -7 - BK - LL - XX