

RADIANCE-B

RDC-B



YYZ Radiance is a custom curved or straight shaped luminaire with aluminum body powder coated in required RAL. The dramatic circular/ linear/ custom shaped profile incorporates direct and indirect lighting which enhances the interior environment and creates an elegant effect within the space. PMMA opal diffuser provides a seamless lighting over the entire length of the fixture. Application areas includes Office spaces, breakout spaces, etc.

FEATURES

| | |
|-----------------|---|
| MATERIAL | Aluminum 6063-T5 |
| FINISH | Black, White, Silver, Gold |
| WORKING VOLTAGE | 220-240V AC / 110-277V AC |
| RATED POWER | 30W, 40W, 50W, 60W, 63W (1120mm dia), 70W, 90W, 110W, 120W, 145W, |
| & DIMENSIONS | 160W, 180W, 200W, 240W, 280W, 320W, 360W, 400W, 480W |
| RADIANCE ANGLE | 120° |
| LAMP LIFE | L80 B50, 100, 000 hours |
| MOUNTING | Pendant, Surface |
| CONNECTION | Indoor rated connections |
| DIMENSIONS | Ø1120 x W 31 x H 50mm |
| OPERATION TEMP | -20° C - +40° C |
| CONTROL | On/Off, 1-10V, Dali |



OSRAM/NICHIA/CREE/SEOUL/CITIZEN
LED Quality


240 VOLT
Working Voltage

63W
Rated power

ELECTRICAL DATA

| | |
|----------------|---------------------------------------|
| SUPPLY VOLTAGE | 220-240VAC |
| COLORS | 2700K, 3000K, 4000K, 6500K, RGB, RGBW |
| CRI | 80, 90 |
| LUMEN | 75lm/W |

DIMENSIONS



ORDERING LOGIC

| PRODUCT | WATTAGE | COLOR TEMPEARTURE | VOLTAGE | CONTROL | FINISH | CRI | CUSTOM |
|---------|--------------|-------------------|--------------|-------------|-------------|---------|--------|
| RDC-B | 30 | 30W (Ø480) | 240 - 240VAC | SW - On/Off | BK - Black | 80 - 80 | xx |
| | 40 | 40W (Ø640) | | DA - Dali | WH - White | | |
| | 50 | 50W (Ø800) | | AN - 1-10V | SL - Silver | 90 - 90 | |
| | 60 | 60W (Ø960) | | | GO - Gold | | |
| | 63 | 63W (Ø1120) | | | | | |
| | 70 | 70W (Ø1120) | | | | | |
| | 90 | 90W (Ø1440) | | | | | |
| | 110 | 110W (Ø1720) | | | | | |
| | 120 | 120W (Ø1910) | | | | | |
| | 145 | 145W (Ø230) | | | | | |
| | 160 | 160W (Ø2550) | | | | | |
| | 180 | 180W (Ø2870) | | | | | |
| | 200 | 200W (Ø3190) | | | | | |
| | 240 | 240W (Ø3820) | | | | | |
| | 280 | 280W (Ø4460) | | | | | |
| | 320 | 320W (Ø5100) | | | | | |
| 360 | 360W (Ø5730) | | | | | | |
| 400 | 400W (Ø6370) | | | | | | |
| 480 | 480W (Ø7640) | | | | | | |

Sample: RDC-B - 30 - CT27 - 240 - SW - BK - 80 - XX