

RADIANCE-C

RDC-C



YYZ Radiance is a custom curved or straight shaped luminaire with aluminum body powder coated in required RAL. The dramatic circular/ linear/ custom shaped profile incorporates direct and indirect lighting which enhances the interior environment and creates an elegant effect within the space. PMMA opal diffuser provides a seamless lighting over the entire length of the fixture. Application areas includes Office spaces, breakout spaces, etc.

FEATURES

MATERIAL	Aluminum 6063-T5
FINISH	Black, White, Silver, Gold
WORKING VOLTAGE	220-240V AC / 110-277V AC
RATED POWER	38W, 50W, 63W, 75W, 88W, 113W, 135W, 150W, 180W,
& DIMENSIONS	200W, 225W, 250W, 300W, 350W, 400W, 450W, 500W, 600W
RADIANCE ANGLE	120°
LAMP LIFE	L80 B50, 100, 000 hours
MOUNTING	Pendant, Surface
CONNECTION	Indoor rated connections
DIMENSIONS	Ø1120 x W 37 x H 60mm
OPERATION TEMP	-20° C - +40° C
CONTROL	On/Off, 1-10V, Dali



OSRAM/NICHIA/CREE/SEOUL/CITIZEN
LED Quality


240 VOLT
Working Voltage

63W
Rated power

ELECTRICAL DATA

SUPPLY VOLTAGE	220-240VAC
COLORS	2700K, 3000K, 4000K, 6500K, RGB, RGBW
CRI	80, 90
LUMEN	75lm/W

DIMENSIONS



ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	VOLTAGE	CONTROL	FINISH	CRI	CUSTOM
RDC-C	38 (Ø480)	(CT27)	240 - 240VAC	SW - On/Off	BK - Black	80 - 80	xx
	50 (Ø640)	(CT30)		DA - Dali	WH - White		
	63 (Ø800)	(CT40)		AN - 1-10V	SL - Silver	90 - 90	
	75 (Ø960)	(CT65)			GO - Gold		
	88 (Ø1120)	(RGB)					
	113 (Ø1440)	(RGBW)					
	135 (Ø1720)						
	150 (Ø1910)						
	180 (Ø230)						
	200 (Ø2550)						
	225 (Ø2870)						
	250 (Ø3190)						
	300 (Ø3820)						
	350 (Ø4460)						
	400 (Ø5100)						
	450 (Ø5730)						
500 (Ø6370)							
600 (Ø7640)							

Sample: RDC-C - 38 - CT27 - 240 - SW - BK - 80 - XX