

LFX NEON 3D SERIES

LFX-O-10.00W-WH-2835-Z1-96-24V-CV-1615-H-1-HT-R-M-S&T-L-W-L5



IP67
WATER
PROOF

CE 10W

YYZ LFX neon 3D waterproof light series flexible dual-bending, horizontal bend and vertical bend both and good color consistency high uv resistance, up to level 4.1, excellent light transmittance, up to 93 %, suitable for curved construction projects, along with other task and specialty applications.




FEATURES

LIGHT SOURCE	2835 Led
LED QUANTITY	96Leds / m
FINISH	White PCB
WORKING VOLTAGE	24 Vdc
RATED POWER	10W / m
RADIANCE ANGLE	120°
LAMP LIFE	50,000 hrs
MOUNTING	Clip, Channel
CONNECTION	Outdoor connector
DIMENSIONS	16x15mm
MAX DAISY RUN	5 m



ELECTRICAL DATA

POWER CONSUMPTION	10W/m
SUPPLY VOLTAGE	24 V dc
COLORS	White
LEDS / 3.3FT	96
LUMEN	42lm/W




ORDERING LOGIC

PRODUCT SERIES	TYPE	POWER	COLOR TEMPERATURE	LED TYPE	BIN	NO. OF LED	BEAM ANGLE	VOLTAGE	CIRCUIT	WIDTH	CRI	NO OF LED ROWS	CONNECTION		
LFX	O - Outdoor	10 - 10W	(WH) White	2835	Z1	96 - 96 LEDs/mtr	120 - 120°	24-24V	CV-Constant voltage	1615 - 16x15mm	H - High (90)	1	HT - Hardwired Tail OC - Outdoor Connector		
										MODEL	COLOR CONTROL	LIGHT EMITTING DIRECTION	LED POWER	PCB COLOR	LENGTH
										R - Regular	M - Mono	S&T - Side & Top	L - Low	W - White	L5 - 5mtr
Sample: LFX-O-10.00-WH-2835-Z1-24-120-24-CV-1615-H-1-OC-R-M-S&T-L5															


LFX NEON 3D SERIES

LFX-O-10.00W-WH-2835-Z1-96-24V-CV-1615-H-1-HT-R-M-S&T-L-W-L5

BENDING DETAILS



Lateral bending



Vertical bending



can twist 360 degrees

ACCESSORY



Waterproof connectors



mounting chain



Aluminum channel



mounting clip

GRAPH

Wavelength of Color Light

