

ATRIUM 1 RECESSED

ATR 1R

IP44 IK06 CE

YYZ Atrium range of modular LED ceiling lights render glare free homogenous light through the use of high quality opal diffuser. Luminaire is provided with suitable mounting brackets required for various types of ceilings. Recommended for wide range of end users from commercial office buildings to high output retail applications.



FEATURES

MATERIAL	CRCA Sheet Steel
FINISH	Epoxy polyester powder coated in white (RAL9016)
RATED POWER	30W, 36W, 40W, 50W, 60W, 75W
WORKING VOLTAGE	220-240V AC
MOUNTING	Ceiling recessed
CONNECTION	Indoor rated connections
LAMP LIFE	L70 B20 50,000hrs
DIMENSION	595mm x 595mm x 65mm, 1195x295x65mm, 1195x595x65mm (Lay-in), 599mm x599mm x 65mm, 1199x299x65mm, 1199x599x65mm (Dampa)
OPERATING TEMP	-20° C - +50° C
CONTROL	On/Off, Dali, 1-10V, Emergency Kit

SAMSUNG/LUMILEDS
LED Quality


220-240VAC
Working Voltage

30W/36W/40W/50W/60W/75W
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	30W, 36W, 40W, 50W, 60W, 75W
SUPPLY VOLTAGE	220-240V AC
COLORS	3000K/4000K/6500K
CRI	>80
DELIVERED LUMENS	130lm/W
SDCM	3 SDCM, 2SDCM (On request)

DIMENSIONS



LAY-IN/GYPSUM CEILING			GYPSUM	METAL CEILING		
L	W	H	CUT-OUT	L	W	H
595	595	65	570X570	599	599	65
1195	295	65	1170X270	1199	299	65
1195	595	65	1170X570	1199	599	65

ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	INPUT VOLTAGE	FINISH	CONTROL	SIZE - L x W	CUSTOM
ATR 1R	30 - 30W	(CT 30) 3000K	220-240VAC	WH - White	SW - On/Off	A - 595x595	XX - XXX
	36 - 36W	(CT 40) 4000K		XX - Custom	DA - Dali	B - 1195x295	
	40 - 40W	(CT 65) 6500K			AN - 1-10V	C - 1195x595	
	50 - 50W	(CTXX) CUSTOM			EM - Emergency Kit	D - 599x599	
	60 - 60W					E - 1199x299	
	75 - 75W					F - 1199x599	

Sample: ATR 1R - 30 - CT30 - 220 - WH - SW - A - XX