LINEAR WALLWASHER



LRW 35C-Mono IP66 IK05 C €

YYZ LRW is wall washer series linear light of new solution for large scale with high brightness architectural illumination. Its streamline design and aluminum profile along with adjustable brackets make it an elegant solution for wall washing and grazing applications. This IP66 rated modular system is available in 300mm, 500mm, or 1000mm lengths and can be customized as per project situations. Its integrated design of heat dissipating structure and degassing valve make it suitable for exterior architectural, retail and hospitality applications.



FEATURES


FINISH	6063 Aluminum
WORKING VOLTAGE	24V DC
RATED POWER	18W, 24W, 36W/mtr
BEAM ANGLE	15°, 30°, 45°, 60°, 15°x60°, 20°x40°
MOUNTING	Surface mounting
OPTIC	РММА
DIMENSIONS	1000(L) x 35(W) x59(H)mm
OPERATION TEMP	-30° C - +50° C
STORAGE TEMP	-40° C - +80° C
WEIGHT	1.2kg
LAMP LIFE	50,000 hrs
BODY COLOR	Aluminum color
CONTROL	On/Off



ELECTRICAL DATA

SUPPLY VOLTAGE	240V ac
COLORS	2700K, 3000K, 4000K, 5000K, 5700K
LUMEN	85-95lm/W

DIMENSION



ORDERING LOGIC

PRODUCT	WATT	AGE	COLOR TEMPERATURE		VOLTAGE	BEAMANGLE		BODY COLOR		CUSTOM	
LRW 35C	18 -	18W	(CT27)	2700K	DC - 24V DC	15	-	15°	AL	- Aluminum	XX - XXX
	24 -	24W	(CT30)	3000K		30	-	30°			
	36 -	36W	(CT40)	4000K		45	-	45°			
			(CT50)	5000K		60	-	60°			
			(CT57)	5700K		15x60	-	15°x60°			
						20x40	-	20°x40°			

Sample: LRW 35C - 18 - CT27 - DC -15 - AL - XX