

PANDORA MAGNETIC TRACK LIGHT

PDA

Mono IP40 CE

Pandora series of Track light features a family of attachments to meet diverse lighting requirements. Tools free magnetic insets includes spotlight, cylindrical & circular pendants, wall wash spot, linear downlight and diffused lights. Preferred choice for wide range of commercial, architectural and hospitality spaces.



FEATURES

MATERIAL	Aluminum + PC
BODY FINISH	Black, White
RATED POWER	36W
BEAM ANGLE	120°
VOLTAGE	220-240VAC, 50/60Hz
MOUNTING	Track mounted
DIMENSIONS	868x22x24mm
OPERATION TEMP	-20° C - +50° C
CONTROL	On/Off, Dali, 1-10V


BRIDGELUX
LED Quality

36W
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	36W
SUPPLY VOLTAGE	220-240VAC
COLORS	2700K, 3000K, 4000K, 5000K
CRI	90
LUMEN	85lm/W

DIMENSIONS



ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	CONTROL	BEAMANGLE	FINISH	CUSTOM	
PDA	36 - 36W	(CT27)	2700K	ND - Non Dimmable	120 - 120°	BK - Black	XX - XX
		(CT30)	3000K	DA - Dali		WH - White	
		(CT40)	4000K	AN - 1-10V			
		(CT50)	5000K				

Sample: PDA - 36 - CT30 - ND - 120 - BK - XX