# OAK ROUND SMALL DC SPEC SHEET

# OAK-R-S-DC
















Our OAK series LED spotlight fixtures are a simple, yet elegant solution for architectural spot and accent luminaire. Available with three optic configurations (Narrow, Medium & Wide). The luminaire is capable of withstanding extreme outdoor conditions with a chemically sealed glass lens and proprietary moisture barriers.

#### **SPECIFICATION**

LIGHT SOURCE

OPERATING VOLTAGE 100 - 240 VDC OPERATING TEMPERATURE -20°C to + 50°C

CRI 80 INPUT CURRENT@12 VDC 420 mA INPUT CURRENT @24 VDC 220 mA NO OF LED 1 LED TYPE SMD

**COLOR RANGE** 2700K / 3000K / 3500K / 4000K

Samsung

**PROJECTION** Narrow, Medium, Wide

FIXTURE CONNECTION Pigtail **AVAILABLE IP RATING** IP66












# **DELIVERED LUMENS BY CCT**

White	Lumens (5W)
2700K	310 lm
3000K	310 lm
3500K	310 lm
4000K	310 lm





180° Angle Swivel Base




# OAK ROUND SMALL DC SPEC SHEET

OAK-R-S-DC



# **ORDERING CODE**



CT 35 - 3500K WB - WIDE CT 40 - 4000K

BODY FINISH

TRIM FINISH

BWH - WHITE TWH - WHITE

BBL - BLACK TBL - BLACK

BSL - SILVER TSL - SILVER

BCM - CUSTOM TGL - GOLD

TCM - CUSTOM

Sample: OAK-R-S-5W-CT27-NB-SM-DC-H-BWH-TBL

#### **DIMENSIONS**










# PHOTOMETRIC DATA


# Polar Curve



# BIN Details (CIE 1931)



# Spectral Radiant Flux VS Wavelength



# **RELATED PRODUCTS**

Spike Mount



OAK - Round Small - AC

