

# FRAME POLE LIGHT

## FAE-PL

**Mono** IP65 CE

Frame pole light is suitable for exterior and pathway lighting in public spaces. The efficient technology ensures a glare free orientation and guidance for passers-by and vehicles drivers with maximum visual comfort. The slim and sleek design makes an architectural element in itself.



### FEATURES

HOUSING	Heavy duty die-cast aluminium
WORKING VOLTAGE	100-240V ac
MOUNTING	Ground mounted
DIMENSIONS	Ø180x1000, 1200, 4000(H)mm
OPTIC	Type 2, Type 3, Type 4 light distribution available
OPERATION TEMP	-20° C - +50° C
BODY COLOR	Black, Grey
LAMP LIFE	50,000 hrs
CONTROL	On/Off
IP RATING	IP 65

CREE/LUMILEDS/BRIDGELUX  
LED Quality

100-240V AC  
Working Voltage

28W /39W/52W  
Rated power

### ELECTRICAL DATA

RATED POWER	28W, 39W, 52W
COLORS	3000K, 4000K, 6000K
CRI	80
LUMEN	90-95lm/W

### DIMENSION



### ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	OPTIC	CONTROL	FINISH
F AE-PL	28 - 28W	(CT30) 3000K	T2 - Type 2 Distribution	ND - Non Dimmable	BK - Black
	39 - 39W	(CT40) 4000K	T3 - Type 3 Distribution		GR - Grey
	52 - 52W	(CT60) 6000K	T4 - Type 4 Distribution		

Sample: FAE-PL - 28 - CT30 - T2 - ND - BK