

# LED FLOOD LIGHT SQUARE SPEC SHEET



LFL-Q-212S MONO



The LFL-Q-212S Mono offers a versatile lighting solution with its 8.35"x 8.35" (212 mm x 212 mm) modular lens, providing a range of available angles for various applications. Its minimalist exterior design ensures ease of construction and installation. With exceptional flexibility and scalability, the LFL-QS is well-suited for a wide array of environments while maintaining reliable performance.

## SPECIFICATION

<b>OPERATING VOLTAGE</b>	120-220V AC
<b>RATED POWER</b>	100W
<b>LEAKAGE CURRENT</b>	Max 0.7mA
<b>DOWN-LEAD SPEC</b>	3*1mm <sup>2</sup> Ø7.2mm (L=350mm)
<b>CONTROL</b>	Switch
<b>LIGHT SOURCE</b>	OSRAM
<b>NO OF LED</b>	30
<b>CCT</b>	2700K, 3000K, 4000K, 5000K, 5700K, 6500K
<b>BEAM ANGLE</b>	8°, 15°, 30°, 45°, 60°, 15X60°
<b>LUMEN RANGE</b>	50 to 55 lm/W
<b>SDCM</b>	≤5
<b>CRI</b>	≥80
<b>MATERIAL</b>	ADC12 Aluminum
<b>COLOR FINISH</b>	Black, grey, white
<b>ROTATION ANGLE</b>	180°
<b>DIMENSIONS</b>	8.35" x 4.96" x 11.28" (212 mm x 126 mm x 286.4 mm)
<b>NET WEIGHT</b>	3.1 kg
<b>LENS</b>	PC
<b>OPERATING TEMPERATURE</b>	-30°C to +50°C
<b>STORAGE TEMPERATURE</b>	-40°C to +80°C
<b>AVAILABLE IP RATING</b>	IP66
<b>IMPACT RATING</b>	IK07



**V** 120-220V AC  
Operating Voltage

**W** 100W  
Rated power

## ORDERING CODE

PRODUCT SERIES	TYPE	SIZE	POWER	COLOR TEMPERATURE	BEAM ANGLE	FIXTURE FINISHING	VOLTAGE	ACCESSORIES
LFL - LED Flood Light	Q - Square	212S	100W - 100 Watts	CT27 - 2700K	8D - 8°	BK - Black	AC - 120-220V AC	N - None
				CT30 - 3000K	15D - 15°	GY - Grey		H - Hood
				CT40 - 4000K	30D - 30°	WH - White		
				CT50 - 5000K	45D - 45°	XX - Custom*		
				CT57 - 5700K	60D - 60°			
				CT60 - 6000K	15x60D - 15x60°			

Sample: LFL-Q-212S-100W-CT27-15D-BK-AC-H

"\*" represent special order, please contact factory for detail.

## Expansion Setup





# LED FLOOD LIGHT SQUARE SPEC SHEET

LFL-Q-212S MONO







## DIMENSIONS

**LFL-Q-212S**  
Net Weight: 3.1 kg




**Visor  
(Optional)**




## PHOTOMETRIC DATA


**8 Degrees**




**15 Degrees**




**30 Degrees**



**45 Degrees**



**60 Degrees**



**15x60 Degrees**

