VERTEX 32.5 RGB & RGBW SPEC SHEET TX-32.5







YYZ Vertex series is a new surface mounted frameless slim shape weatherproof luminaire in soft and high LED or RGBW version specially designed for facade and in unique structure design shape. This series are designed to offer functional, a wide range of lighting solutions and dramatic highlighting of the architectural facades of different buildings, malls through the linear curved design with superior finishing as well highest efficiency with a long service life.


SPECIFICATION

| OPERATING VOLTAGE | 24V DC, 48V DC | | | |
|-----------------------|---|--|--|--|
| RATED POWER | 15W | | | |
| DOWN-LEAD SPEC | 2*1.0mm² + 3*0.3mm² | | | |
| CONTROL | DMX512 | | | |
| SEGMENT/CHANNEL | 4 Pixel Address / 16 Channels per 1200mm length | | | |
| CONTROL CHIP | SM17500P | | | |
| ADDRESS METHOD | Signal Cable | | | |
| LED QUANTITY | 60 pcs | | | |
| COLOR | RGBW (2700K/3000K/4000K/5000K/5700K) | | | |
| BEAM ANGLE | 150° | | | |
| LUMENS | 290 lm | | | |
| SDCM | ≥5 | | | |
| BODY MATERIAL | Alu 6063 | | | |
| LENS MATERIAL | PC | | | |
| COLOR FINISH | Anodized finish | | | |
| ROTATION ANGLE | ±90° (Adjustable bracket) | | | |
| DIMENSIONS | 1000 mm (L) x 32.5 mm (W) x 44 mm (H) | | | |
| | 39.37 in. (L) x 1.28 in. (W) x 1.73 mm (H) | | | |
| WEIGHT | 0.7 kg | | | |
| OPERATING TEMPERATURE | -40°C to + 50°C | | | |
| STORAGE TEMPERATURE | -40°C to + 80°C | | | |
| IP RATING | IP66 | | | |




DIMENSIONS






FLAT BRACKET

VTX 2.0 FLAT DIFFUSER FLAT BRACKET





32.5




VTX 2.0 ROUND DIFFUSER ROTATED BRACKET




VTX 2.0 ROUND DIFFUSER FLAT BRACKET

ŕ






VTX 2.0 ROUND DIFFUSER CLIP BRACKET



CLIP BRACKET





VTX 2.0 FLAT DIFFUSER CLIP BRACKET



ROTATED BRACKET

YYZ Lighting Inc., 1175 Squires Beach Rd., Unit 2, Pickering, ON, Canada. L1W 3V3 www.yyzlighting.com

VERTEX 32.5 RGB & RGBW SPEC SHEET

VTX-32.5



ORDERING CODE

| DIFFUSER | POWER | OPTIC | COLOR TEMPERATURE | VOLTAGE | FIXTURE LENGTH | CONTROL | BODY COLOR | BRACKET TYPE |
|----------|----------|------------|----------------------|--------------------------------------|--|---|---|--|
| - Flat | 15 - 15W | 150 - 150° | (RGB) RGB | 24 - 24V DC | 30 - 300mm | DMX - DMX | BK - Black | RB - Rotated Bracket |
| - Round | | | (RGBW) RGBW | 48 - 48V DC | 50 - 500mm | | GR - Grey | FB - Flat Bracket |
| | | | | | 100 - 1000mm | | WH - White | CB - Clip Bracket |
| | | | | | | | | |
| | | | | | | | | |
| | | | | - Flat 15 - 15W 150 - 150° (RGB) RGB | - Flat 15 - 15W 150 - 150° (RGB) RGB 24 - 24V DC | - Flat 15 - 15W 150° (RGB) RGB 24° 24V DC 30° - 300mm - Round - - - (RGBW) RGB 48° 48V DC 50° - 500mm | - Flat 15 - 15W 150 - 150° (RGB) RGB 24 - 24V DC 30 - 300mm DMX - DMX - Round | - Flat 15 - 15W 150 - 150° (RGB) RGB 24 - 24V DC 30 - 300mm DMX - DMX BK - Black - Round - Flat - 660 - |

Sample: VTX-32.5-F-15-150-RGB-24-30-DMX-BK-RB

PHOTOMETRIC DATA

