## VERTEX 32.5 RGB & RGBW SPEC SHEET





IP66 WATER PROOF



YYZ Vertex series is a new surface mounted frameless slim shape weatherproof luminaire in soft and high LED or RGBW version specially designed for facade and in unique structure design shape. This series are designed to offer functional, a wide range of lighting solutions and dramatic highlighting of the architectural facades of different buildings, malls through the linear curved design with superior finishing as well highest efficiency with a long service life.

#### **SPECIFICATION**

**OPERATING VOLTAGE** 24V DC, 48V DC

RATED POWER 15W

**DOWN-LEAD SPEC** 2\*1.0mm<sup>2</sup> + 3\*0.3mm<sup>2</sup>

CONTROL DMX512

SEGMENT/CHANNEL 4 Pixel Address / 16 Channels per 1000mm length

CONTROL CHIP SM17500P

ADDRESS METHOD Signal Cable

LED QUANTITY 60 pcs

**COLOR** RGBW (2700K/3000K/4000K/5000K/5700K)

BEAM ANGLE 150°

LUMENS 290 lm

SDCM ≥5

BODY MATERIAL Alu 6063

LENS MATERIAL PC

COLOR FINISH Anodized finish

**ROTATION ANGLE** ±90° (Adjustable bracket)

**DIMENSIONS** 1000 mm (L) x 32.5 mm (W) x 44 mm (H)

39.37 in. (L) x 1.28 in. (W) x 1.73 mm (H)

**WEIGHT** 0.7 kg

**OPERATING TEMPERATURE** -40°C to +50°C **STORAGE TEMPERATURE** -40°C to +80°C

IP RATING IP66



LIGHTING









## **DIMENSIONS**

#### ROTATED BRACKET











#### FLAT BRACKET











## CLIP BRACKET











# VERTEX 32.5 RGB & RGBW SPEC SHEET

VTX-32.5



#### **ORDERING CODE**

PRODUCT	[	DIFFUSER		POWER		OPTIC		COLOR TEMPERATURE		VOLTAGE		FIXTURE LENGTH			CON	TROL	BODY COLOR		BRACKET TYPE			
VTX-32.5	F	-	Flat	15	- 1	15W	150	-	150°	(RGB)	RGB	24 -	24V DC	30	-	300mm	DMX	- DMX	BK	- Black	RB - Re	otated Bracket
	R	-	Round							(RGBW)	RGBW	48 -	48V DC	50	-	500mm			GR	- Grey	FB -	Flat Bracket
														100	-	1000mm			WH	- White	CB -	Clip Bracket

Sample: VTX-32.5-F-15-150-RGB-24-30-DMX-BK-RB

### **PHOTOMETRIC DATA**

